

80kW Hash Generator

SPECIFICATION SHEET

Genset Specifications

Electrical	Prime Power Rating	113kW
	Continuous Power Rating ¹	79kW
	Voltage	416-480V P-P, 240-277V P-N, WYE
	Frequency	60Hz
	Full Load Current	196A (416V), 118A (480V)
	Power Factor Rating	.8PF
	Alternator Efficiency	93.7%
	Main Circuit Breaker Rating	250A, 80% Continuous
Engine	Manufacturer	Power Solutions International
	Displacement	6.7L
	Cylinder Arrangement	Inline, 6-Cylinder
	Aspiration	After cooled, forced induction
	Engine Horsepower Rating	162HP
	Fuel Type	Natural Gas
	EPA Certification	Optional
Fuel	Inlet Pressure	5 PSI Min, 25 PSI Max, 15 PSI Nominal
	Inlet Connection	1" NPT Female
Fuel Consumption²	100%	32 MCFD
	75%	24 MCFD
	50%	16 MCFD

Loadcenter Specifications

Cooling	Intake Fan Quantity	1
	Intake Fan Flow Rate	20,500 CFM
	Intake Fan Motor Rating	5 HP
	VFD Rating	10 HP
Racks	Quantity	1
	PDU Outlets	24 - PA45(P33) 6-Pin
	PDU Outlet Rating	25A, 80% Continuous
	Shelf Quantity Per Rack	4
	Shelf Dimension	51.9" x 12" (W x H)
	ASIC Compatibility ³	M30, M50, M60, S21, S21 Pro, S21 XP
Ancillary Load	Cooling Maximum	3.5kW
	Networking, Control & Lighting	0.5kW

Building Specifications

Building	Type	Steel building (self-framer, skid mounted)
	Handling	Lifting lugs / eyes in skid base
	Access	(2) Steel man-doors w/ panic hardware
	Dimensions	16' x 5' x 9.5' (L x W x H)
	Weight	7,500LBS (Estimated)

80kW Hash Generator

SPECIFICATION

SHEET

Product Features

Standard	<ul style="list-style-type: none"> Power distribution switch gear Networking hardware (unmanaged) Heat management attachments Smart PDU's (Power Distribution Unit) Fuel gas scrubber LoadSync™ with HMI control screen
Loadcenter	<ul style="list-style-type: none"> Elevated ASIC racking, preventing debris from reaching ASIC's Up to 24 ASICs per rack Powered exhaust dampeners, keeping ASIC's safe when not in operation 4' wide center aisle for ample working space and safe egress Intakes have external pre filter and internal primary filter Each intake fan has an electrical disconnect for safe service Direct drive motors per intake fan for minimal maintenance and more reliability Intake fan motors are in the cold section of the building, not subject to high ASIC exhaust Fan speed fully automated or manually controlled through LoadSync™
LoadSync™	<ul style="list-style-type: none"> Remote control and monitoring of the entire system Engine and electrical real time data Cooling fan automation and control PDU automation and load control ASIC monitoring Historical data trends and alarm history

Product Options

- Sound attenuating liner & attachments
- Custom building colors
- Hospital grade mufflers
- Downgrade to basic PDUs
- Removal of LoadSync™ system
- Certification Label (CAN/US)
- *Other customizations available upon request*

¹Total loading should target the continuous power rating for the best overall operational efficiency. Use the formula, Total Loading = (Continuous Power Rating – Ancillary Load) / ASIC Load Rating. ASIC clocking may need to be adjusted to operate at full PDU outlet capacity. In low ambient conditions, where the cooling fans are not required, higher ASIC load might be possible.

²Fuel consumption is based on a proportional relationship with prime power output, assuming optimal efficiency conditions. These estimates are provided to assist in planning and operational efficiency. Actual fuel consumption will vary based on specific operating conditions.

³ASIC compatibility is based on published specifications from WhatsMiner and Antminer. Upstream data is not responsible for ASIC suppliers not adhering to their published specifications (e.g., higher power consumption, increased air flow requirements, etc.). Contact sales for other ASIC compatibility.

Ratings and performance are solely for reference only and subject to site conditions and Upstream Data application and ratings guidelines. All information is subject to change without notice.